




MOBY 40 Gas-Engine PowerBoard (C.A.R.B. Tier II Approved)

Powered By...
Tanaka
High Performance 2-Stroke Engines

PB-SE803 Specifications:



> 40cc Tanaka PureFire® Low-Emission Engine
Saves you up to 30 percent in fuel costs and allows you to travel over 30 miles on one tank of gas.

> Locking Steering Stem and Folding Handle
Provides maximum stability in both the riding and transporting positions.

> Dual Belt Drive System
Provides quick and smooth acceleration in both wet and dry terrain.

> Centrifugal Clutch Transmission
Prevents the unit from moving upon ignition as well as allows you to manually move it when off.

> Large, Air-Filled Tires
Provides you with the smoothest, most comfortable ride.

Top Speed:	24-25mph
Engine:	Tanaka® PureFire® EPA & CARB Approved
Displacement:	40 cc
Drive System:	Dual Belt SMOOTH DRIVE
Transmission:	Centrifugal Clutch
Starting:	Recoil Starter
Range:	Over 30 miles With the 33 fl. oz. tank
Brakes:	Rear Friction / Front Disc Caliper
Wheels:	Composite Core Split Rim
Tires:	10" Kenda 4-Ply Slick Pneumatic
Dimensions:	41" H, 16" W, 48" L
Construction:	High Tensile Steel Frame with Durable Wood Deck
Max Rider Wt.:	270 lbs.
Dry Weight:	52 lbs.

Note: Actual product configuration may differ from the image shown.

Don't Forget Accessories...



Marketed in the OPE Industry By:

Tanaka America / ISM, Inc. 1028 4th Street SW / "B" • Auburn, WA 98001 • Web site: tanaka-usa.com

Updated 12-12-02